

SADPA MPD HANDGUN CLASSIFIER			
Scoring	Limited		
Round Count	28		
Concealment	Optional	Rules	SADPA MPD 2019.V2
Targets	2 x MPD Paper Targets		
Start Signal	Timer	Stop Signal	Last Shot Fired
Muzzle Safe	180° Degree Rule		

CLASSIFIER DRILLS				
String	Rounds	Start Position	Start Condition	Procedure
1	4	SP1	Standing upright with hands relaxed at sides and firearm loaded.	On Signal , Engage all targets with two rounds each to the head.
2	6	SP1	Standing upright with hands relaxed at sides and firearm loaded with three rounds only.	On Signal , Engage T1 with two rounds to the body and one round to the head, reload and engage T2 with two rounds to the body and one round to the head.
3	4	SP1	Standing upright with hands relaxed at sides and firearm loaded.	On Signal , Engage all targets with one round each strong hand only, transition to weak hand and re-engage all targets with one round each weak hand only.
4	6	SP2	Standing upright with hands relaxed at sides and firearm loaded. Shooter may start at either SP2.	On Signal , Engage T1 from SP2 with three rounds, move to opposite SP2, engage T2 with three rounds.
5	4	SP3	Standing upright with hands relaxed at sides and firearm loaded.	On Signal , Engage all targets with two rounds each.
6	4	SP3	Standing upright with hands relaxed at sides and firearm loaded.	On Signal , Engage all targets with two rounds each from around low cover.

CLASSIFIER TIMES				
Division	Master	Expert	Marksman	Novice
Service Pistol (SP15) Service Pistol Limited (SP10) Optics and Lasers (OLP)	< 28.00	< 47.00	< 69.00	≥ 69.00
Compact Pistol (CP)	< 29.40	< 48.50	< 70.35	≥ 70.35
Defensive Pistol (DP)	< 30.25	< 49.90	< 72.35	≥ 72.35
Revolver (REV)	< 35.00	< 57.75	< 83.74	≥ 83.74
Ultra-Compact (UC)	< 32.20	< 53.15	< 77.05	≥ 77.05
Rimfire (22P)	< 25.20	< 41.55	< 60.30	≥ 60.30

STAGE BUILDING NOTES:
<ol style="list-style-type: none"> Targets must be positioned so that the top of the target is at one-point-five (1.5m) meters. Distance between targets must be three (3m) meters. This is the distance from the edges of the targets. Green lines indicate the cover fault lines to be used. Cover line must be aligned from the edge of the drum to the center of the targets as indicated. Cover line may not extend more than one (1m) meter past the edge of the drum. SP1 indicates a shooting box that is an approximate measurement of one-meter by one-meter (1x1m) where the front edge is at the five (5m) meter mark. SP2 indicates shooting boxes that is an approximate measurement of one-meter by one-meter (1x1m) where the front edges are at the ten (10m) meter mark and the distance between the inner edges of the boxes are five (5m) meter apart. SP3 indicates a drum where the rear edge of the drum is at the fifteen (15m) meter mark.

Target height: 1.5m

